

PROFESSIONAL
LIGHTING
FOR THE
PERFORMING ARTS

Product catalogue 2023



Fresnel

Luminaires with fresnel lens, adjustable yoke and optical zoom.

Recommended for soft and even lighting.

Available with motorized yokes with DMX control or pole operated yokes.

FN LED 50

Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-76° (2,5kg - 27x16x25cm)

FN HY LED 100

Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-75° (3,5kg - 29x22x31cm)



FN HY LED 200

Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	14°-81° (6,0kg - 35x30x36cm)

FN HY LED 200 Tunable

Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	13°-50° (7,5kg - 39x30x45cm)

FN HY LED 200 RGBW

Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	13°-50° (7,5kg - 39x30x45cm)

FN HY LED 200 6C

Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	13°-50° (7,5kg - 39x30x45cm)

FN HY LED 300

Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	09°-45° (9,5kg - 43x30x48cm)

FN HY LED 300 Tunable

Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	09°-45° (9,5kg - 43x30x48cm)

FN HY LED 300 RGBW

Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	12°-45° (9,5kg - 43x30x48cm)

FN HY LED 300 6C

Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	12°-45° (9,5kg - 43x30x48cm)

FN HY LED 700

Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)

FN HY LED 700 Tunable

Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)

FN HY LED 700 8C (6C + Tunable)

Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)

MI FN NO

Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,3kg - 11x13x17cm)

COM 12 F

Source	Halogen
Power	1000/1200W (GX 9,5)
Version	07°-53° (5,4kg - 20x20x30cm)

COM 25 F

Source	Halogen
Power	2000/2500W (G 22)
Version	07°-65° (10,8kg - 27x29x41cm)

Plano-Convex

Luminaires with prism-convex lens, adjustable yoke and optical zoom.
Recommended for soft and accent lighting.
Available with motorized yokes with DMX control or pole operated yokes.

PC LED 50	
Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	08°-80° (3,0kg - 27x16x29cm)

PC HY LED 100	
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	15°-75° (3,5kg - 29x22x31cm)



PC HY LED 200	
Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	16°-87° (6,0kg - 35x30x36cm)

PC HY LED 200 Tunable	
Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	15°-50° (7,5kg - 39x30x45cm)

PC HY LED 200 RGBW	
Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	15°-50° (7,5kg - 39x30x45cm)

PC HY LED 200 6C	
Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	15°-50° (7,5kg - 39x30x45cm)

PC HY LED 300	
Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	06°-45° (12,5kg - 47x30x57cm)

PC HY LED 300 Tunable	
Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	06°-45° (12,5kg - 47x30x57cm)

PC HY LED 300 RGBW	
Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	08°-45° (12,5kg - 47x30x57cm)

PC HY LED 300 6C	
Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	08°-45° (12,5kg - 47x30x57cm)

PC HY LED 700	
Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)

PC HY LED 700 Tunable	
Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)

PC HY LED 700 8C (6C + Tunable)	
Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)

MI PC NO	
Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,6kg - 11x13x22cm)

COM 12 PC	
Source	Halogen
Power	1000/1200W (GX 9,5)
Version	04°-63° (6,8kg - 20x20x40cm)

COM 25 PC	
Source	Halogen
Power	2000/2500W (G 22)
Version	04°-66° (13,7kg - 27x29x53cm)

Profile

Luminaires with adjustable shutters, yoke, optical zoom and focus.
Recommended for accent and precise lighting, as well as for images projection (gobos).
Available with motorized yokes with DMX control or pole operated yokes.

PR LED 50

Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	20°-40° (4,1kg - 37x37x43cm)

PR HY LED 100

Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Versions	20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)



PR HY LED 200

Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 200 Tunable

Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 200 RGBW

Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 200 6C

Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 300

Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 300 Tunable

Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 300 RGBW

Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 300 6C

Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 700

Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Versions	08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)

PR HY LED 700 Tunable

Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)

PR HY LED 700 8C (6C + Tunable)

Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Versions	08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)

MI PR ZS NO

Source	Halogen
Power	300W (GY 9,5)
Versions	20°-40° (1,3kg - 11x13x17cm)

COM 12 ZS/ZM

Source	Halogen
Power	1000/1200W (GX 9,5)
Versions	13°-35° (9,8kg - 20x20x72cm) 24°-50° (9,1kg - 20x20x57cm)

COM 25 ZS/ZW

Source	Halogen
Power	2000/2500W (G 22)
Versions	09°-25° (25,1kg - 27x29x90cm) 17°-36° (21,3kg - 27x29x79cm)

Followspot

Luminaires with adjustable shutters, yoke, optical zoom and focus. Built-in manual colour changer included in LED versions.

Recommended for accent and long distance lighting, with direct control from the operator.



FS HY LED 300	
Power	300W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	07°-14° (19,0kg - 35x35x100cm)

FS HY LED 700	
Power	700W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	07°-14° (36,0kg - 42x40x144cm)



VD 25 M HR	
Source	Discharge
Power	2500W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	30-100 m
Version	05°-13° (51,0kg - 27x29x163cm)

Floodlight

Asymmetric

For the illumination of large areas and cycloramas. Suitable both for lighting from the floor and from the top.

DOM 1000

Source	Halogen
Power	1000/1250W (R7s)
Version	3,8kg - 29x28x21cm





Asymmetric

Asymmetric cyclorama powered by LED source in RGBW. Thanks to its sophisticated specifically designed optical system, it allows to illuminate in an absolutely even way an area of over 40 sqm when positioned at a distance from the backdrop of only 1,5m.



CYC LED 300 RGBW

300W
RGBW
- DMX-RDM
- Local
15,0kg - 25x57x43cm



Professional lighting for the performing arts since 1969

Downlight

Recessed LED luminaires with high-efficiency white chip. High quality polycarbonated aluminate optics.

	HAL LED 85
Power	85W (no fan)
LED	White (3000K, 4000K, 5600K)
Control	- DALI - Local - DMX-RDM (opt.)
Versions	29° (0,75kg - 16x16x14cm) 46° (0,75kg - 16x16x14cm) 72° (0,75kg - 16x16x14cm)



Professional lighting for the performing arts since 1969

Pinspot

Architectural pinspot with integrated LED source.



SUPERLUT LED 30

Power	30W, 230V, 230VAC
LED	White (3000K, other on request)
Control	- Dimmable from mains

SUPERLUT (for halo and no-dimmable LED)

max 75W, 12V, R-111
Lamp not included

Versions	15° (1,5kg - 18x16x22cm)
	26° (1,5kg - 18x16x22cm)

(depends on mounted lamp)



Professional lighting for the performing arts since 1969

Pole Operated system

Pole Operated yokes: modular system of yokes with 2 o 3 functions (tilt, pan and focus) with safet clutch to protect gear box and to allow hand focusing



ARC system

Automated Remote Control: motorised DMX modular yokes for high precision 16 bit focusing for tilt, pan, beam adjustment. Thanks to the modular structure it accepts all LED and Conventional Spotlight fixtures and most of the luminaires commercially available on the market.



Ed. 05.2023



Operational Headquarters

Via Sardegna, 3 - 20098 - S. Giuliano Milanese (MI) - Italia

www.spotlight.it

Registered Office

Via Martino Anzi 8, 22100 Como (CO) - Italia