

PROFESSIONAL
LIGHTING
FOR THE
PERFORMING ARTS

Product catalogue 2024



Fresnel

Luminaires with fresnel lens, adjustable yoke and optical zoom.
Recommended for soft and even lighting.
Available with motorized yokes with DMX control or pole operated yokes.



FN LED 50	
Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-76° (2,5kg - 27x16x25cm)

FN HY LED 100	
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	12°-75° (3,5kg - 29x22x31cm)

FN HY LED 100 Tunable	
Power	100W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	12°-60° (3,5kg - 29x22x31cm)

FN HY LED 100 RGBW	
Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	12°-60° (3,5kg - 29x22x31cm)

FN HY LED 100 6C	
Power	100W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	12°-60° (3,5kg - 29x22x31cm)

FN HY LED 200	
Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	14°-81° (6,0kg - 35x30x36cm)

FN HY LED 200 Tunable	
Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	13°-50° (7,5kg - 39x30x45cm)

FN HY LED 200 RGBW	
Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	13°-50° (7,5kg - 39x30x45cm)

FN HY LED 200 6C	
Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	13°-50° (7,5kg - 39x30x45cm)

FN HY LED 300	
Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	09°-45° (9,5kg - 43x30x48cm)

FN HY LED 300 Tunable	
Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	09°-45° (9,5kg - 43x30x48cm)

FN HY LED 300 RGBW	
Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	12°-45° (9,5kg - 43x30x48cm)

FN HY LED 300 6C	
Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	12°-45° (9,5kg - 43x30x48cm)

FN HY LED 700	
Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)

FN HY LED 700 Tunable	
Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)

FN HY LED 700 8C (6C + Tunable)	
Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)

MI FN NO	
Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,3kg - 11x13x17cm)

COM 12 F	
Source	Halogen
Power	1000/1200W (GX 9,5)
Version	07°-53° (5,4kg - 20x20x30cm)

COM 25 F	
Source	Halogen
Power	2000/2500W (G 22)
Version	07°-65° (10,8kg - 27x29x41cm)

Plano-Convex

Luminaires with prism-convex lens, adjustable yoke and optical zoom.
Recommended for soft and accent lighting.
Available with motorized yokes with DMX control or pole operated yokes.



PC LED 50	
Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	08°-80° (3,0kg - 27x16x29cm)

PC HY LED 100	
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	15°-75° (3,5kg - 29x22x31cm)

PC HY LED 100 Tunable	
Power	100W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	15°-60° (3,5kg - 29x22x31cm)

PC HY LED 100 RGBW	
Power	100W
LED	RGBW
Control	- DMX-RDM - Local
Version	15°-60° (3,5kg - 29x22x31cm)

PC HY LED 100 6C	
Power	100W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	15°-60° (3,5kg - 29x22x31cm)

PC HY LED 200	
Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	16°-87° (6,0kg - 35x30x36cm)

PC HY LED 200 Tunable	
Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	15°-50° (7,5kg - 39x30x45cm)

PC HY LED 200 RGBW	
Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Version	15°-50° (7,5kg - 39x30x45cm)

PC HY LED 200 6C	
Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	15°-50° (7,5kg - 39x30x45cm)

PC HY LED 300	
Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	06°-45° (12,5kg - 47x30x57cm)

PC HY LED 300 Tunable	
Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	06°-45° (12,5kg - 47x30x57cm)

PC HY LED 300 RGBW	
Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	08°-45° (12,5kg - 47x30x57cm)

PC HY LED 300 6C	
Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Version	08°-45° (12,5kg - 47x30x57cm)

PC HY LED 700	
Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)

PC HY LED 700 Tunable	
Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)

PC HY LED 700 8C (6C + Tunable)	
Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)

MI PC NO	
Source	Halogen
Power	300W (GY 9,5)
Version	07°-53° (1,6kg - 11x13x22cm)

COM 12 PC	
Source	Halogen
Power	1000/1200W (GX 9,5)
Version	04°-63° (6,8kg - 20x20x40cm)

COM 25 PC	
Source	Halogen
Power	2000/2500W (G 22)
Version	04°-66° (13,7kg - 27x29x53cm)

Profile

Luminaires with adjustable shutters, yoke, optical zoom and focus.
Recommended for accent and precise lighting, as well as for images projection (gobos).
Available with motorized yokes with DMX control or pole operated yokes.

PR LED 50	
Power	50W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Version	20°-40° (4,1kg - 37x37x43cm)



PR HY LED 100	
Power	100W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Versions	20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)

PR HY LED 100 Tunable	
Power	100W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)

PR HY LED 100 RGBW	
Power	100W
LED	RGBW
Control	- DMX-RDM - Local
Versions	20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)

PR HY LED 100 6C	
Power	100W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)

PR HY LED 200	
Power	200W
LED	White (3000K, 4000K, 5600K)
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 200 Tunable	
Power	200W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 200 RGBW	
Power	200W
LED	RGBW
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 200 6C	
Power	200W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)

PR HY LED 300	
Power	300W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 300 Tunable	
Power	300W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 300 RGBW	
Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 300 6C	
Power	300W
LED	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local
Versions	15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)

PR HY LED 700	
Power	700W
LED	White (3200K, 5600K)
Control	- DMX-RDM - Local
Versions	08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)

PR HY LED 700 Tunable	
Power	700W
LED	White (2700K-6500K)
Control	- DMX-RDM - Local
Versions	08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)

PR HY LED 700 8C (6C + Tunable)	
Power	700W
LED	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local
Versions	08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)

MI PR ZS NO	
Source	Halogen
Power	300W (GY 9,5)
Versions	20°-40° (1,3kg - 11x13x17cm)

COM 12 ZS/ZW	
Source	Halogen
Power	1000/1200W (GX 9,5)
Versions	13°-35° (9,8kg - 20x20x72cm) 24°-50° (9,1kg - 20x20x57cm)

COM 25 ZM/ZW	
Source	Halogen
Power	2000/2500W (G 22)
Versions	09°-25° (25,1kg - 27x29x90cm) 17°-36° (21,3kg - 27x29x79cm)

Followspot

Luminaires with adjustable shutters, yoke, optical zoom and focus. Built-in manual colour changer included in LED versions.

Recommended for accent and long distance lighting, with direct control from the operator.



FS HY LED 300	
Power	300W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	07°-14° (19,0kg - 35x35x100cm)

FS HY LED 700	
Power	700W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	04°-14° (36,0kg - 42x40x144cm)



VD 25 M HR	
Source	Discharge
Power	2500W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	30-100 m
Version	05°-13° (51,0kg - 27x29x163cm)



Floodlight

Asymmetric

Asymmetric cyclorama powered by LED source in RGBW. Thanks to its sophisticated specifically designed optical system, it allows to illuminate in an absolutely even way an area of over 40 sqm when positioned at a distance from the backdrop of only 1,5m.

CYC LED 300 RGBW

Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	15,0kg - 25x57x43cm



Perfect also for TV Studios



Pole operated yoke (PO system)



Pantograph



Asymmetric

For the illumination of large areas and cycloramas.
Suitable both for lighting from the floor and from the top.



DOM 1000

Source	Halogen
Power	1000/1250W (R7s)
Version	3,8kg - 29x28x21cm

Downlight

HALLED Series has the ability to transform the look and feel of a space by introducing a high quality white light, designed for a wide range of different applications such as Orchestra shell, House, Working spaces, Shop windows, Malls, Museums, Exhibitions, Art galleries but also TV Studios, Cinemas, Theatres.

HALLED is the ideal solution for installations where silence, energy saving and maintenance cost reduction are key factors.



HAL LED 85	
Power	85W (no fan)
LED	White (3000K, 4000K, 5600K)
Control	- DALI - Local - DMX-RDM (opt.)
Versions	29° (0,75kg - 16x16x14cm) 46° (0,75kg - 16x16x14cm) 72° (0,75kg - 16x16x14cm)



Pinspot



SERIE LUT

SERIE CANOVA

Pinspot

Pinspot

Pinspot
Pinspot zoom

Profile zoom



stand alone
(230V)

stand alone
(230V)

on track
(230V)



SUPERLUT (for halo and no-dimmable LED)

SUPERLUT LED 30

Power max 75W, 12V, R-111
LED Lamp not included
Control

30W, 230V, 230VAC
White (3000K, other on request)
- Dimmable from mains

Versions (depends on mounted lamp)

10°, 15°, 26° (1,5kg - 18x16x22cm)

stand alone
(230V)

on track
(230V)

on track
(48V)



DALI-CASAMBI
converter



DALI-CASAMBI
converter

CANOVA LED 30 with PSU

Power 30W, 230V
LED White (3000K, other on request)
Control - DMX
- DALI (on request)
- CASAMBI (on request, for track)

Versions Pinspot: 10°, 15°, 26°
Pinspot zoom: 15°-45°
Profile zoom: 20°-40°

CANOVA LED 30 with track adaptor

Power 30W, 48V
LED White (3000K, other on request)

- DALI
- CASAMBI (on request)
Pinspot: 10°, 15°, 26°
Pinspot zoom: 15°-45°
Profile zoom: 20°-40°

Pole Operated system

Pole Operated yokes: modular system of yokes with 2 or 3 functions (tilt, pan and focus) with safet clutch to protect gear box and to allow hand focusing



ARC system

Automated Remote Control: motorised DMX modular yokes for high precision 16 bit focusing for tilt, pan, beam adjustment. Thanks to the modular structure it accepts all LED and Conventional Spotlight fixtures and most of the luminaires commercially available on the market.



Ed. 02.2024



Operational Headquarters
Via Sardegna, 3 - 20098 - S. Giuliano Milanese (MI) - Italia

www.spotlight.it

Registered Office
Via Martino Anzi 8, 22100 Como (CO) - Italia