

PROFESSIONAL
LIGHTING
FOR THE
PERFORMING ARTS




Product catalogue 2025









Fresnel



Luminaires with fresnel lens, adjustable yoke and optical zoom.
Recommended for soft and even lighting.
Available with motorized yokes with DMX control or pole operated yokes.



	FN HY LED 100	FN HY LED 100 Tunable 	FN HY LED 100 RGBW 	FN HY LED 100 6C 
Power	100W	100W	200W	100W
LED	White (3000K, 4000K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	12°-75° (3,5kg - 29x22x31cm)	12°-60° (3,5kg - 29x22x31cm)	12°-60° (3,5kg - 29x22x31cm)	12°-60° (3,5kg - 29x22x31cm)

	FN HY LED 200	FN HY LED 200 Tunable 	FN HY LED 200 RGBW 	FN HY LED 200 6C 
Power	200W	200W	200W	200W
LED	White (3000K, 4000K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	14°-81° (6,0kg - 35x30x36cm)	13°-50° (7,5kg - 39x30x45cm)	13°-50° (7,5kg - 39x30x45cm)	13°-50° (7,5kg - 39x30x45cm)

	FN HY LED 300	FN HY LED 300 Tunable 	FN HY LED 300 RGBW 	FN HY LED 300 6C 
Power	300W	300W	300W	300W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	09°-45° (9,5kg - 43x30x48cm)	09°-45° (9,5kg - 43x30x48cm)	12°-45° (9,5kg - 43x30x48cm)	12°-45° (9,5kg - 43x30x48cm)

	FN HY LED 700	FN HY LED 700 Tunable 	FN HY LED 700 8C (6C + Tunable) 
Power	700W	700W	700W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	11°-53° (18,0kg - 50x40x60cm)	11°-53° (18,0kg - 50x40x60cm)	11°-53° (18,0kg - 50x40x60cm)

	MI FN NO	COM 12 F	COM 25 F
Source	Halogen	Halogen	Halogen
Power	300W (GY 9,5)	1000/1200W (GX 9,5)	2000/2500W (G 22)
Version	07°-53° (1,3kg - 11x13x17cm)	07°-53° (5,4kg - 20x20x30cm)	07°-65° (10,8kg - 27x29x41cm)

Plano-Convex

Luminaires with prism-convex lens, adjustable yoke and optical zoom.
Recommended for soft and accent lighting.
Available with motorized yokes with DMX control or pole operated yokes.



	PC HY LED 100	PC HY LED 100 Tunable	PC HY LED 100 RGBW	PC HY LED 100 6C
Power	100W	100W	100W	100W
LED	White (3000K, 4000K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	15°-75° (3,5kg - 29x22x31cm)	15°-60° (3,5kg - 29x22x31cm)	15°-60° (3,5kg - 29x22x31cm)	15°-60° (3,5kg - 29x22x31cm)

	PC HY LED 200	PC HY LED 200 Tunable	PC HY LED 200 RGBW	PC HY LED 200 6C
Power	200W	200W	200W	200W
LED	White (3000K, 4000K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	16°-87° (6,0kg - 35x30x36cm)	15°-50° (7,5kg - 39x30x45cm)	15°-50° (7,5kg - 39x30x45cm)	15°-50° (7,5kg - 39x30x45cm)

	PC HY LED 300	PC HY LED 300 Tunable	PC HY LED 300 RGBW	PC HY LED 300 6C
Power	300W	300W	300W	300W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGBW	RGB+AMBER+CYAN+LIME
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	06°-45° (12,5kg - 47x30x57cm)	06°-45° (12,5kg - 47x30x57cm)	08°-45° (12,5kg - 47x30x57cm)	08°-45° (12,5kg - 47x30x57cm)

	PC HY LED 700	PC HY LED 700 Tunable	PC HY LED 700 8C (6C + Tunable)
Power	700W	700W	700W
LED	White (3200K, 5600K)	White (2700K-6500K)	RGB+AMBER+CYAN+LIME+WW+CW
Control	- DMX-RDM - Local	- DMX-RDM - Local	- DMX-RDM - Local
Version	13°-54° (20,0kg - 50x40x69cm)	13°-54° (20,0kg - 50x40x69cm)	13°-54° (20,0kg - 50x40x69cm)

	MI PC NO	COM 12 PC	COM 25 PC
Source	Halogen	Halogen	Halogen
Power	300W (GY 9,5)	1000/1200W (GX 9,5)	2000/2500W (G 22)
Version	07°-53° (1,6kg - 11x13x22cm)	04°-63° (6,8kg - 20x20x40cm)	04°-66° (13,7kg - 27x29x53cm)

Profile

Luminaires with adjustable shutters, yoke, optical zoom and focus.
Recommended for accent and precise lighting, as well as for images projection (gobos).
Available with motorized yokes with DMX control or pole operated yokes.



	PR HY LED 100 Power 100W LED White (3000K, 4000K, 5600K) Control - DMX-RDM - Local Versions 20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)	PR HY LED 100 Tunable Power 100W LED White (2700K-6500K) Control - DMX-RDM - Local Versions 20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)	PR HY LED 100 RGBW Power 100W LED RGBW Control - DMX-RDM - Local Versions 20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)	PR HY LED 100 6C Power 100W LED RGB+AMBER+CYAN+LIME Control - DMX-RDM - Local Versions 20°-38° (6,2kg - 40x34x54cm) 35°-50° (6,0kg - 40x34x45cm)
	PR HY LED 200 Power 200W LED White (3000K, 4000K, 5600K) Control - DMX-RDM - Local Versions 15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)	PR HY LED 200 Tunable Power 200W LED White (2700K-6500K) Control - DMX-RDM - Local Versions 15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)	PR HY LED 200 RGBW Power 200W LED RGBW Control - DMX-RDM - Local Versions 15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)	PR HY LED 200 6C Power 200W LED RGB+AMBER+CYAN+LIME Control - DMX-RDM - Local Versions 15°-30° (11,5kg - 47x34x76cm) 25°-50° (11,0kg - 47x34x64cm)
	PR HY LED 300 Power 300W LED White (3200K, 5600K) Control - DMX-RDM - Local Versions 15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)	PR HY LED 300 Tunable Power 300W LED White (2700K-6500K) Control - DMX-RDM - Local Versions 15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)	PR HY LED 300 RGBW Power 300W LED RGBW Control - DMX-RDM - Local Versions 15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)	PR HY LED 300 6C Power 300W LED RGB+AMBER+CYAN+LIME Control - DMX-RDM - Local Versions 15°-30° (15,0kg - 47x34x76cm) 25°-50° (14,0kg - 47x34x64cm)
	PR HY LED 700 Power 700W LED White (3200K, 5600K) Control - DMX-RDM - Local Versions 08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)	PR HY LED 700 Tunable Power 700W LED White (2700K-6500K) Control - DMX-RDM - Local Versions 08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)	PR HY LED 700 8C (6C + Tunable) Power 700W LED RGB+AMBER+CYAN+LIME+WW+CW Control - DMX-RDM - Local Versions 08°-25° (31,0kg - 47x40x127cm) 20°-40° (28,0kg - 47x40x92cm)	

	MI PR ZS NO Source Halogen Power 300W (GY 9,5) Versions 20°-40° (1,3kg - 11x13x17cm)	COM 12 ZS/ZW Source Halogen Power 1000/1200W (GX 9,5) Versions 13°-35° (9,8kg - 20x20x72cm) 24°-50° (9,1kg - 20x20x57cm)	COM 25 ZM/ZW Source Halogen Power 2000/2500W (G 22) Versions 09°-25° (25,1kg - 27x29x90cm) 17°-36° (21,3kg - 27x29x79cm)
--	--	---	---

Followspot

Luminaires with adjustable shutters, yoke, optical zoom and focus. Built-in manual colour changer included in LED versions.

Recommended for accent and long distance lighting, with direct control from the operator.



FS HY LED 300	
Power	300W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	07°-14° (19,0kg - 35x35x100cm)

FS HY LED 700	
Power	700W
LED	White (5600K)
Control	- DMX-RDM - Local
Version	04°-14° (36,0kg - 42x40x144cm)



VD 25 M HR	
Source	Discharge
Power	2500W / MSR (G 38)
Standard	Hot Restrike version, Iris diaphragm with black out, shaping shutters and slots for B size gobo holder
Distance	30-100 m
Version	05°-13° (51,0kg - 27x29x163cm)



Floodlight

Asymmetric

Asymmetric cyclorama powered by LED source in RGBW. Thanks to its sophisticated specifically designed optical system, it allows to illuminate in an absolutely even way an area of over 40 sqm when positioned at a distance from the backdrop of only 1,5m.

CYC LED 300 RGBW

Power	300W
LED	RGBW
Control	- DMX-RDM - Local
Version	15,0kg - 25x57x43cm



Perfect also for TV Studios



Pole operated yoke (PO system)



Pantograph



Asymmetric

For the illumination of large areas and cycloramas.
Suitable both for lighting from the floor and from the top.



DOM 1000

Source	Halogen
Power	1000/1250W (R7s)
Version	3,8kg - 29x28x21cm

Downlight

HALLED Series has the ability to transform the look and feel of a space by introducing a high quality white light, designed for a wide range of different applications such as Orchestra shell, House, Working spaces, Shop windows, Malls, Museums, Exhibitions, Art galleries but also TV Studios, Cinemas, Theatres.

HALLED is the ideal solution for installations where silence, energy saving and maintenance cost reduction are key factors.




HAL LED 85

Power	85W (no fan)
LED	White (3000K, 4000K, 5600K)
Control	- DALI - Local - DMX-RDM (opt.)
Versions	29° (0,75kg - 16x16x14cm) 46° (0,75kg - 16x16x14cm) 72° (0,75kg - 16x16x14cm)



Architectural



Pinspot

stand alone
(230V)



SUPERLUT LED 30

Power	30W, 230V, 230VAC
LED	White (2700K, 3000K, 4000K, other on request)
Control	- Dimmable from mains

Versions Pinspot: 10°, 15°, 26°, 36°, 60°

on track
(230V)



stand alone
(230V)



CANOVA LED 30

Power	30W, 230V
LED	White (2700K, 3000K, 4000K)
Control	- DMX - DALI (on request)

Versions Pinspot: 10°, 15°, 26°, 36°, 60°
Pinspot zoom: 15°-45°

on track
(230V)
(48V)



DALI-CASAMBI
converter

Power	30W, 230V or 48V
LED	White (2700K, 3000K, 4000K)
Control	- DALI - CASAMBI (on request)

Versions Pinspot: 10°, 15°, 26°, 36°, 60°
Pinspot zoom: 15°-45°

Profile

stand alone
(230V)



CANOVA LED 30

Power	30W, 230V
LED	White (2700K, 3000K, 4000K)
Control	- DAMX - DALI (on request)

Versions Profile zoom: 20°-40°

on track
(230V)
(48V)



DALI-CASAMBI
converter

Power	30W, 230V or 48V
LED	White (2700K, 3000K, 4000K)
Control	- DALI - CASAMBI (on request)

Versions Profile zoom: 20°-40°

Pole Operated system

Pole Operated yokes: modular system of yokes with 2 or 3 functions (tilt, pan and focus) with safet clutch to protect gear box and to allow hand focusing



ARC system

Automated Remote Control: motorised DMX modular yokes for high precision 16 bit focusing for tilt, pan, beam adjustment. Thanks to the modular structure it accepts all LED and Conventional Spotlight fixtures and most of the luminaires commercially available on the market.





Operational Headquarters
Via Sardegna, 3 - 20098 - S. Giuliano Milanese (MI) - Italia

www.spotlight.it

Registered Office
Via Martino Anzi 8, 22100 Como (CO) - Italia